



MERCURY AIR 20

PREMIUM RUBBER 20 BAR AIR ISO2398-4A









BRANDING: MERCURY 20 AIR/WP 20BAR ISO2398 4A-SIZE QTR/YR

COLOUR: BLACK

TEMP: -40°C to +70°C

PRODUCT INFORMATION

Order Ref	RAH-SIZE MM
Tube:	SYNTHETIC RUBBER INNER
Reinforcement:	HIGH TENSILE SYNTHETIC TEXTILE
Cover:	ABRASION, OZONE AND WEATHER RESISTANT SMOOTH NATURAL AND SYNTHETIC RUBBER
Application:	MEDIUM DUTY SERVICE FOR AIR AND PNEUMATIC TOOLS SPECIFICALLY IN MINES, QUARRIES AND CONSTRUCTION
Specification:	TS 745 / EN ISO 2398 TYPE 4/A

									
INCH	MM	MM	BAR	PSI	BAR	PSI	MM	GR/M	M
1/4	6	13	20	290	60	870	60	130	25/100
5/16	8	16	20	290	60	928	80	190	25/100
3/8	10	18	20	290	60	870	100	230	25/50/100
1/2	13	22	20	290	60	870	130	333	25/50/100
3/4	19	30	20	290	60	928	190	580	25/50
1	25	36	20	290	60	870	250	730	25/50



-40°C to +70°C

www.integraflex.co.uk

Contact Us Today...

01642244160

email: info@integraflex.co.uk

- >> 100+ years experience in the hose & fittings industry
- >> Competitive pricing, excellent quality, quick turnaround
- >> Large stocks for rapid response
- >> Full traceability on most assemblies
- >> ISO 9001 & 14001 ACCREDITED

Integraflex Ltd, 72 Jay Avenue, Teesside Industrial Estate, Thornaby, TS17 9LZ