






HILCOFLEX

RUBBER COVERED MULTIPURPOSE HOSE

BRANDING: HILCOFLEX COLOUR: BLACK TEMP: -20°C to +80°C

PRODUCT INFORMATION

| | |
|----------------|---|
| Order Ref | HIL-SIZE-MM |
| Tube: | SMOOTH FOR MINIMUM FRICTION LOSS |
| Reinforcement: | HIGH TENACITY POLYESTER WARP AND POLYAMIDE/POLYSTER WEFT GIVING HIGH TENSILE STRENGTH |
| Cover: | HIGH GRADE FORMULATION NBR/PVC COMPUND EXTRUDED IN ONE STEP PRODUCTION PRO- |
| Application: | FOR CONSTRUCTION SITES, AGRICULTURE, MINING, WATER TRANSFER AND COMPRESSED AIR. FOR IRRIGATION, LIGHTWEIGHT SEWER CLEANING AND CABLE COVER PROTECTION |

| |  ID | WALL THICKNESS |  WP |  WP |  BP | BREAKING STRENGTH |  W/A |  COIL |
|-------|--|----------------|--|--|--|-------------------|---|--|
| INCH | MM | MM | BAR/PSI | MAX. BAR/PSI | BAR/PSI | KG | GR/MT | MTR |
| 2 | 52 | 2.5 | 16/230 | 20/290 | 50/725 | 3.9 | 400 | 100 |
| 2 1/2 | 65 | 2.5 | 16/230 | 20/290 | 50/725 | 4.3 | 540 | 100 |
| 3 | 76 | 2.9 | 16/230 | 20/290 | 50/725 | 6.5 | 650 | 100 |
| 4 | 102 | 3.3 | 16/230 | 20/290 | 50/725 | 9.5 | 1000 | 100 |
| 5 | 127 | 3.5 | 14/205 | 17/245 | 42/610 | 17 | 1400 | 100 |
| 6 | 152 | 3.7 | 14/205 | 17/245 | 42/610 | 17.9 | 1800 | 100 |
| 8 | 203 | 3.9 | 10/145 | 12/175 | 30/435 | 26.9 | 2600 | 100 |



-20°C to +80°C

www.integraflex.co.uk

Contact Us Today...

01642244160

email: info@integraflex.co.uk

- >> 100+ years experience in the hose & fittings industry
- >> Competitive pricing, excellent quality, quick turnaround
- >> Large stocks for rapid response
- >> Full traceability on most assemblies
- >> ISO 9001 & 14001 ACCREDITED